

DESCRIPTION: ROVAL NATURAL STONE SOLUTIONS 281 PLUS ENHANCER is designed to brighten and enhance the natural colors of the surface to which it is applied. 281 PLUS ENHANCER dries clear, producing an invisible barrier that resists both water and oil based contaminants. 281 PLUS ENHANCER is non-yellowing and is suitable for interior and exterior applications.

RECOMMENDED FOR USE ON: All porous, tumbled, distressed, flamed and textured natural stone, such as slate, tumbled marble, unfinished granite, limestone, flagstone, sandstone and terracotta. 281 PLUS ENHANCER is suitable for counter tops, floors, walls, back splashes, vanities and shower stalls.

NOT RECOMMENDED FOR USE ON: Polished granite or marble surfaces and other impervious surfaces, such as glass, metal, ceramic tile, porcelain, plastic, vinyl, painted or varnished surfaces, synthetic and solid surfaces. Do not use on wood or fabric.

SURFACE PREPARATION: Always apply this product to a clean and dry surface, free from all dirt, loose debris, dust, grease, wax, oil, cleaning compounds, silicone, previous treatments and all foreign material.

APPLICATION INSTRUCTIONS: *Read and understand the entire label before proceeding or attempting to apply this product. Always test this product on the surface to which it is to be applied to ensure suitability and before approving for your intended use.* 281 PLUS ENHANCER is supplied ready-to-use and should be applied using a chemical resistant brush, sponge lambswool applicator, or a white absorbent cloth. Work in small areas and apply sealer slowly, in a uniform and even manner, leaving no puddles or voids. Apply sparingly onto dense surfaces, wait 5-10 minutes and remove any material not absorbed by buffing until dry using a clean, absorbent cloth. On highly porous surfaces, apply liberally and allow to stand for 10 to 15 minutes. Buff off excess until dry using a clean and dry cotton towel. If more enhancement is desired, reapply within 15 minutes and repeat the above steps. Allow treated surface to cure 24 hours before subjecting to use.

LIMITATIONS: Extreme weather conditions and the use of strong cleaning solutions or solvents can adversely affect the performance of this product.

MAINTENANCE: Sweep, vacuum or dust mop floors often. Damp mop floors or wipe treated surfaces with a solution of 2 oz. ROVAL TILE & STONE CLEANER mixed with one gallon of clean water. Remove all spills as soon as possible with a clean, dry, absorbent cloth. Use a mild soap and water solution to remove oily residues. The use of strong detergents can adversely affect the performance of this product. Periodic applications of this product may be necessary to maintain desired protection.

APPROXIMATE COVERAGE IN SQUARE FEET PER GALLON: Actual application rates will vary due to the different porosity levels and the variety of surfaces on which this product can be used. Porous clay tile: 30. Tumbled and honed stone: 150. Grout: 250.

PACKAGE SIZE: 12/1 quart case, 4/1 gallon case.

TECHNICAL PROFILE:

Viscosity:	Similar to Water
Solvent:	Aliphatic
Active Solids:	11 to 12%
Density:	0.68
Appearance:	Clear Straw Colored Liquid
Shipping Category:	Butyl Acetate Solution
V.O.C.:	720.25 Grams/Liter



***Oil & Water Repellent ♦ Interior/Exterior ♦ Enhances Natural Colors ♦
For Use On Dense and Porous Surfaces ♦ Makes Cleaning Easier ♦
Easily Recoated For Additional Protection ♦ Controls Efflorescence***