

**PRODUCT DESCRIPTION:** ROVAL REFLECTA POLISH is a highly durable, water base acrylic floor polish, designed to protect and maintain the finish of newly sealed and existing natural stone, masonry and clay tile installations. REFLECTA POLISH is self-leveling, self-polishing and produces a deep, high gloss, “wet look” finish without buffing. REFLECTA POLISH helps protect floors from the daily wear and tear of foot traffic and damage caused by scuffmarks, marring and black heel marks. REFLECTA POLISH is slip resistant and is suitable for both commercial and residential walking surfaces. REFLECTA POLISH exhibits excellent recoatability without excessive build up and can provide years of lasting beauty and protection when used correctly.

**RECOMMENDED FOR USE ON:** Floors sealed with ROVAL SEALER 1044, SEALER 1088, HGS-450 AND SABER SEAL. Use on sealed Mexican Saltillo clay pavers, epoxy sealed surfaces, slate, terrazzo, quarry tile, natural stone, flamed and textured stone, unfinished marble, rough finished granite and most other non-glazed tiles and composition floors. REFLECTA POLISH is for use on interior surfaces only.

**NOT FOR USE ON:** This product is not intended for use on glazed or impervious surfaces such as glass, metal, ceramic tile, polished marble, granite or surfaces of similar density.

**SURFACE PREPARATION:** Always apply this product to a clean and dry surface free from any dirt, dust, debris, silicones, waxes, and oils. Make sure all old wax build up has been completely re-moved before applying REFLECTA POLISH. For heavy duty cleaning and removal of wax and dirt build up, use a solution of ROVAL NU-CLEAN CONCENTRATE CLEANER mixed with equal parts clean water. Consult the NU-CLEAN CONCENTRATE CLEANER label for proper use.

**APPLICATION INSTRUCTIONS:** Always test this product in a small area on the surface to which it is to be applied before approving it for your intended use. Apply REFLECTA POLISH using a lint free cot-ton or rayon mop, a sponge or a lambswool applicator. Do not apply with a paint roller. Apply REFLECTA POLISH in a thin, uniform and even manner, leaving no puddles or voids. Apply side to side, overlapping each stroke. Do not rub the polish excessively while applying, as this may cause excessive foam or bubbles. Several coats may be applied, but two are usually sufficient. Allow three hours between applications.

**MAINTENANCE FOR FLOORS:** ROVAL REFLECTA POLISH is made from state-of-the-art chemical technology and raw material ingredients, which allow it to be highly durable, yet easily removed for re-pair with conventional wax removers, such as ROVAL NU-CLEAN CONCENTRATE CLEANER. Use a medium abrasive scrubbing pad, if necessary, to aid in removing polish. For regular maintenance, sweep, dust mop or vacuum often to remove sand, grit and debris. Damp mop with a solution of 2 ounces ROVAL TILE & STONE CLEANER mixed with one gallon clean water. Follow TILE & STONE CLEANER label for use. Apply REFLECTA POLISH to high traffic areas when wear pat-terns develop and to the surrounding area “as needed” in order to maintain the level of performance that best suits your needs. Allow polish to dry several hours before exposing floor to light foot traffic.

**IMPORTANT:** Do not use acids of any kind before or after the use of this product. Acids or their residues can severely affect the performance of this product, especially while in a liquid state, causing it to discolor and peel. If acid is used before or after the application of REFLECTA POLISH, the pH of the surface must be neutralized immediately with a solution of 6 ounces ROVAL NU-CLEAN CONCENTRATE CLEANER mixed with one gallon of clean water. Follow by clean water rinsing and allowing floor to dry. Do not use household cleaning solutions on this finish and follow all maintenance recommendations.

#### SPECIAL NOTES:

1. Do not apply REFLECTA POLISH if the room temperature, the floor or materials are below 55° F.
2. Do not pour unused portion back into the original container.
3. Clean all tools immediately after use with soap and warm water.

#### SPECIAL PRECAUTIONS:

- A. KEEP FROM FREEZING.
- B. USE ON INTERIOR SURFACES ONLY.
- C. DO NOT APPLY TO WET SURFACES.
- D. KEEP AWAY FROM CHILDREN.

**COVERAGE:** Although the actual coverage rates will vary this product will average approximately 1000-1500 square feet per gallon.

**PACKAGE SIZE:** 12/1 quart case, 6/1 gallon case, 5 gallon pail, 30 and 55 gallon drums

#### TECHNICAL PROFILE:

Viscosity:	Water Thin
Solvent:	Water
Active Solids:	22%
Spec. Gravity:	1
Appearance:	Milky White Liquid
Shipping Category:	Non Hazardous
V.O.C.:	N.D.



*Water Based ♦ Slip Resistant ♦ Self Leveling ♦ High Gloss ♦ Easily Repaired ♦ Resists Scuffing & Black Heel Marks*