

**PRODUCT DESCRIPTION:**

ROVAL STEP 2 TERRAZZO SEALER & BRIGHTENER is specially designed to restore and protect terrazzo floors. STEP 2 TERRAZZO SEALER brightens and enhances the natural beauty of the terrazzo marble chips, leaving them with a new luster and revived color. STEP 2 TERRAZZO SEALER dries clear, is non-yellowing and helps protect the floor from the effects of acid, bleach, grease, oil, food, pet soiling and most common household stains. STEP 2 TERRAZZO SEALER prepares the terrazzo floor for the application of ROVAL STEP 3 TERRAZZO FLOOR POLISH.

**RECOMMENDED FOR USE ON:**

Terrazzo, South American clay pavers, domestic quarry tile, wire cut and smooth brick pavers, unfinished and tumbled marble, unfinished granite, slate, travertine, Mexican fossil stone (Consuela and Tecul; honed and polished), flagstone, natural stone, exposed aggregate and similar types of dense surfaces. This product is not intended for use on ceramic tile, polished marble, Mexican Saltillo or surfaces with similar density.

**SURFACE PREPARATION:**

All surfaces must be clean, dry and porous. Surface must be free of all loose debris, dirt, dust, grease, silicones, waxes, oils, cleaners and foreign material. To insure a clean surface, clean the floor area with ROVAL STEP 1 TERRAZZO HEAVY DUTY CLEANER & WAX REMOVER as per label directions.

**DIRECTIONS FOR USE:**

STEP 2 TERRAZZO SEALER can be applied with a lambswool applicator, a lint free mop or a chemical resistant sponge. Apply STEP 2 TERRAZZO SEALER in small areas (approximately 50 to 100 square feet) at a time. Spread the sealer in a slow, even and uniform manner, over-lapping each stroke. Do not leave any puddles or voids. Allow the sealer to dry at least four to six hours before applying a second coat. Allow the last coat of sealer to dry for at least twenty-four hours before finishing the floor with two coats of ROVAL STEP 3 TERRAZZO FLOOR POLISH.

**COVERAGE IN SQUARE FEET PER GALLON:**

First coat 650; Second coat 850.

**PACKAGE SIZE:**

6/1 gallon case, 5 gallon pail and 55 gallon drum.

**SPECIAL NOTES:**

1. Dispose of all application tools by allowing them to dry film onto newspaper before throwing out.
2. Dispose of all empty containers properly and according to all federal, state and local regulations. Dispose of only in a facility authorized to receive hazardous waste.
3. Always wear protective clothing, chemical resistant gloves and protective eyewear.
4. Always provide adequate ventilation when using this product. If not or if area is enclosed, use a NIOSH/MSHA approved respirator suitable for use with solvents.
5. Extinguish all pilot lights and sources of ignition.

**SPECIAL PRECAUTIONS:**

Caution! Combustible!

Contains petroleum distillates - harmful or fatal if swallowed.

As with any chemical compound, read and understand the product's Material Safety Data Sheet (MSDS) before initial use.

Keep away from children!

**IN CASE OF INHALATION:** Move victim away from exposure and into fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet and get immediate medical attention.

**IN CASE OF SKIN CONTACT:** Re-move contaminated clothing. Thoroughly wash area with soap and water. If skin surface is damaged, apply a clean dressing. If irritation persists, get medical attention. Clean and launder contaminated clothing before reuse.

**IN CASE OF EYE CONTACT:** Move victim away from exposure and into fresh air. If redness or irritation develops, wash with large amounts of water for at least fifteen minutes while holding eyelids apart to ensure adequate rinsing of the entire eye surface. Get medical attention.

**IN CASE OF INGESTION:** If swallowed, seek emergency medical treatment. Do not induce vomiting. Aspiration into the lungs due to vomiting may cause chemical pneumonitis, which can be fatal. If victim is drowsy or unconscious, place on left side with head down. Keep victim warm and quiet. Get medical attention. If possible, do not leave victim unattended.

**TECHNICAL PROFILE:**

Viscosity:	Light Syrup
Solvent:	Aliphatic
Active Solids:	16%
Spec. Gravity:	0.90
Appearance:	Clear Liquid
Shipping Category:	Not Regulated
V.O.C.:	746.3 Grams/Liter



***Non-Yellowing ♦ Interior/Exterior ♦ Chemical Resistant ♦ Slow Drying For Superior Penetration ♦  
Excellent Adhesion ♦ Brightens & Protects***