

**PRODUCT DESCRIPTION:** ROVAL STONE SAVER is a revolutionary new product designed to seal and protect a variety of dense and porous natural stone, clay and masonry surfaces. STONE SAVER produces an invisible, protective barrier that helps repel cooking oils, grease, water, beverages, food and animal soiling, while leaving the surface unchanged in appearance. STONE SAVER is water based and contains no harsh solvents or fumes, making it both safe and ideal for use by do-it-yourselfers and professionals. STONE SAVER is excellent for use in food service areas, patient care facilities or wherever the use of solvents is restricted or prohibited. STONE SAVER is recommended for use on interior, exterior, residential and commercial applications.

**RECOMMENDED FOR USE ON:** A variety of highly porous, dense, textured, flamed and tumbled natural stone surfaces such as travertine, granite, slate, unfinished marble, quarry tile, brick, cantera, adoquin, flagstone, limestone, saltillo clay tiles, terracotta, cement tiles, concrete, sanded grout and unpainted wood. STONE SAVER is perfect for showers, countertops, bathrooms, kitchens, clay pots, fountains and ornamental stone. Although this product is suitable for tumbled, unfinished and similar textured natural stone surfaces, it is not recommended for use on highly polished marble, metal, glass, plastic or similar impervious surfaces.

**SURFACE PREPARATION:** All surfaces must be clean, dry and porous, free from all loose debris, dirt, dust, grease, silicones, waxes, oils, cleaners, grout releases and foreign material. Clean area with a solution of ROVAL TILE & STONE CLEANER and water. For heavy soiling use ROVAL NU-CLEAN CONCENTRATE CLEANER. Allow area to thoroughly dry before applying sealer.

**DIRECTIONS FOR USE:** Always test this product first in a small area on the surface to which it is to be applied before approving for your intended use, or attempting the entire sealing procedure. Some surfaces may experience slight color enhancement. STONE SAVER can be applied by brush, sponge, lambswool applicator, 1/4 to 1/2 inch nap paint roller, foam roller, clean white absorbent cloth or low pressure hand pump spray equipment. Always apply sealer slowly, in a uniform and even manner leaving no puddles or voids.

**FOR POROUS SURFACES:** Apply sealer liberally. Allow sealer to completely absorb into the surface and re-apply sealer to the same area within 20 minutes. Additional coats can be applied to increase protection on highly porous surfaces. Allow sealer to cure overnight before subjecting area to normal use.

**FOR DENSE SURFACES:** Apply STONE SAVER sparingly. Any material not readily absorbed within 1 to 2 minutes should be removed by buffing until dry with a clean absorbent cloth. Allow sealer to cure overnight before subjecting to normal use.

**FOR USE AS A GROUT RELEASE:** Apply STONE SAVER and allow to dry overnight before attempting the grout procedure. Always test for proper grout release. If grout does not release successfully or staining is evident, clean the surface, allow to dry and apply another coat of STONE SAVER. Allow sealer to thoroughly dry and re-attempt the grout release test until successful. If acid is used to clean area or remove grout smears, haze or residue, neutralize area afterwards with a solution of ROVAL TILE & STONE CLEANER and water. Allow area to dry completely and apply sealer as directed.

**FOR SEALING EXISTING GROUT:** Recommended for use on porous, sanded, unsanded, quarry grade and cement grout mixtures. Not recommended for epoxy grout, grouts sealed with gloss type sealers or other similar impervious surfaces. Thoroughly clean grout with ROVAL FAST ACTING GROUT CLEANER using a stiff bristle brush. Rinse with a solution of clean water and ROVAL TILE & STONE CLEANER and allow grout to completely dry. Seal grout joints with STONE SAVER using a ROVAL GROUT SEALER APPLICATOR, a small tip paint brush or squeeze bottle with a cone tip. Do not allow sealer to dry on the surface of the tile. Wipe off any excess by buffing until dry with a clean absorbent cloth.

**WHEN A GLOSS IS DESIRED:** After applying STONE SAVER, apply ROVAL REFLECTA POLISH until desired level of gloss is achieved. Some surfaces may exhibit an extremely high degree of repellency after being treated with STONE SAVER and may initially reject the floor polish. This can be overcome by lightly abrading the surface with a medium abrasive scrubbing pad before applying the polish. Be sure to remove all loose debris before applying polish.

**MAINTENANCE:** Sweep, dust mop or wipe with a clean cloth often. Wipe up spills as soon as possible with a clean absorbent cloth. Clean with a mild solution of ROVAL TILE & STONE CLEANER and water.

**COVERAGE IN SQUARE FEET PER GALLON:** Highly Porous Surfaces: 75-550. Dense Surfaces: 650-2000.

**PACKAGE SIZE:** 24/1 pint case, 12/1 quart case, 6/1 gallon case, 5 gallon pail, 30 and 55 gallon drums.

**SPECIAL PRECAUTIONS:** Do not aerosolize or atomize under high pressure. As with any chemical compound, read and understand the Material Safety Data Sheet (MSDS) before initial use. Keep away from children. Keep this product from freezing.

#### TECHNICAL PROFILE:

Viscosity:	Water Thin
Solvent:	Water
Appearance:	Straw Colored Liquid
Active Solids:	8.5%
pH:	6.5
Shipping Category:	Non Hazardous



*Water Based ♦ Repels Grease & Oil ♦ Excellent For Grout ♦ Easy To Use ♦ Natural Look ♦ Matte Finish ♦  
Excellent For Use In Food Preparation Areas ♦ Controls Efflorescence*