

**PRODUCT DESCRIPTION:** ROVAL SALTILLO WHITE WASH is a unique blend of acrylic resins, designed to seal and white wash Mexican Salttillo tile in one application. SALTILLO WHITE WASH penetrates deep into the tile, producing a chemical resistant, durable barrier that protects the tiles from sticking grout and seals against most common staining. SALTILLO WHITE WASH is suit-able for interior and exterior tile installations and is available in three shades, Regular for light white wash, Plus for medium white and Super for more white.

**RECOMMENDED FOR USE ON:** Mexican Salttillo tile. This product is not intended for any other surface.

**SURFACE PREPARATION:** All surfaces must be clean, dry, porous and free of all loose debris, dirt, dust, grease, silicones, waxes, oils, cleaners, grout releases and foreign material. Using a medium abrasive scrubbing pad or fine grit sand paper, lightly abrade the surface of the tiles to remove any rough spots. Remove the dust by buffing the surface of the tile with a clean, dry cloth.

**DIRECTIONS FOR USE:**

**NOTES:**

1. Stir SALTILLO WHITE WASH thoroughly before using and periodically during use.
2. Always apply SALTILLO WHITE WASH before floor is grouted.
3. Apply SALTILLO WHITE WASH to the face of the tiles only, being careful not to get sealer on the sides or bottom of the tile.
4. Clean all tools immediately after use with xylene solvent or lacquer thinner.
5. Always test this product first to ensure desired results and suitability for your intended use.

ROVAL SALTILLO WHITE WASH can be applied using a chemical resistant sponge, a bristle paintbrush, a 3/8 inch nap paint roller or white, absorbent, cotton terry cloth rags.

**USING SPONGES, BRUSHES & RAGS:** Apply sealer with either a sponge or paintbrush. Apply liberally, to the point of saturation. There should be wet liquid sealer on the surface of the tiles that will slowly begin to be absorbed. As the white wash begins to be absorbed, buff off the excess from the surface with a clean dry rag until uniform.

**USING A FOAM OR SHORT NAP PAINT ROLLER:** This procedure is best performed by two individuals. Lay several tiles in rows, end to end, on a protective drop cloth. Pour SALTILLO WHITE WASH into a paint-rolling pan. Wet the roller in the white wash and roll it onto the faces of the tiles, to the point of uniform saturation. The second person should follow behind the one rolling and buff in the excess with a clean and dry rag. Allow the white wash to dry overnight before attempting the grout procedure. Always test for proper grout release. If grout does not release or if staining is evident, apply 1 to 2 coats of ROVAL SEALER 1044 to the tiles, following label instructions. Allow sealer to dry overnight and re-attempt the grout release test.

**AFTER GROUTING:**

For Interior Finishes: After all grout joints and tiles have completely dried, apply two coats of ROVAL SEALER 1044 over the entire floor area. Follow label instructions for proper application procedures. Allow the last coat of sealer to dry at least 3 hours and apply two coats of ROVAL REFLECTA POLISH to the entire area as per label directions.

For Exterior Finishes: After tile and grout joints have dried completely, apply 2 coats of ROVAL SEALER 1044 over the entire area according to the label instructions.

**COVERAGE:** 75-100 Sq. Ft. per gallon.

**PACKAGE SIZE:** 4/1 gallon case and 5 gallon pail.

**SPECIAL PRECAUTIONS:**

Danger! Flammable! Contains petroleum distillates - harmful or fatal if swallowed.

Always wear protective clothing, i.e. chemical resistant gloves, protective eyewear, etc. Always provide adequate ventilation when using this product. If not, a NIOSH approved respirator must be used. Read and understand the product's Material Safety Data Sheet (MSDS) before initial use. Always use caution when working around plants and animals. Care should be taken to protect surrounding areas.

Keep away from children!

**TECHNICAL PROFILE:**

REGULAR

Viscosity: Light Syrup  
Solvent: Aromatic  
Active Solids: 23%  
Spec. Gravity: 0.94  
Shipping Category: Flammable Liquids -  
NOS (Xylene)  
V.O.C.: 726.6 Grams/Liter

PLUS

Viscosity: Medium Syrup  
Solvent: Aromatic  
Active Solids: 24.5%  
Spec. Gravity: 0.96  
Shipping Category: Flammable Liquids -  
NOS (Xylene)  
V.O.C.: 731.1 Grams/Liter

SUPER

Viscosity: Medium/Heavy Syrup  
Solvent: Aromatic  
Active Solids: 25.5%  
Spec. Gravity: 0.99  
Shipping Name: Flammable Liquids  
- NOS (Xylene)  
V.O.C.: 747.7 Grams/Liter



**Seals & White Washes In One Application ♦ Available In Three Shades: Regular, Plus & Super ♦ Interior/Exterior ♦ Non-Yellowing ♦ Chemical Resistant ♦ Superior Bonding ♦ Quick Drying**